

## **ARTICLES TABLE:**

1

Е

F

BIOS Nr.	TITLE	PLATING
24-02538	USB-3.0-9B-T1-BL-TR	15µ´´ selctive Gold plating
24-02539	USB-3.0-9B-T1-AL-TR	30µ´´ selctive Gold plating

2

	Critical Dimensions to be inspected 100%.				NFIL	DEN		
	Critical Dimensions.		RoHS compliant acc. to direct The information contained in this					
	itical Dimensions. determine Cmk &	ermine Cmk & Cpk.			Any reproduction in part or whole is prohibited.			
UNLESS OTHERW DIMENSIONS ARE			$\triangle$	RE	VISION DI	ESCRIPTIC		
TOLERANCES:	xx ±0.10 xxx ±0.05	lG <u>+</u> 1°						
.xxxx ±0.03 ORDER / ARTICLE NO. See Table		002	50 M					
			DO NOT SCALE I					
					ID	DAT		
	ANGLE PRO	JECTION:	CRE	ATED	MEZ	16.01.2		
	16		MOI	DIFIED	T098	14.04.2		
		FIRST		EASED	T011	14.04.2		
WEIGHT: 1.50	)		SUB	RFV02	T098	19 04 2		

Yamaichi acts with all markings of the product exclusively on behalf of the customer as service provider and not as distributor. Yamaichi is not aware of the customer's end use/application. The customer indemnifies Yamaichi from any liability towards third parties in connection with the marking - with the exception of the legal exclusions of liability according to § 309 No. 7 BGB.

3

4

7	8	
l:		A
PBT,UL94V-0 Rated rass (USB 3.0),Phos <sub>j</sub> ss	ohor Bronze (USB 2.0)	
Resistance: 1000 MΩ esistance: 30 mΩ Ma Withstanding Voltage ating: 1.5 AMP ating:30V AC Temperature: 0°C ~ \$	x. : 100V AC for 1 Minute.	В
e: USB B Type. tacts: 9 Contacts. ⁄ersion: Straight Type Type: Female. Color: Blue. ating: See Table : Tray.	9.	С

## ITIAL

## **Customer Drawing**

D

ective 2011/65/EU Specification/Drawing subject to alteration without prior notice. s drawing is the sole property of YAMAICHI ELECTRONICS DEUTSCHLAND GMBH. le without the written permission of YAMAICHI ELECTRONICS DEUTSCHLAND GMBH

