


2 3 WEIGHT: SUBREV04 T153



| 1 | 2 | 3 | 4 | 5 | 6 |  |
|---|---|---|---|---|---|--|

| Nomination                 | Y-Con             | Y-ConJack-31 Y-ConJ |                 | Y-ConJack-32 Y-ConJack-33 (Version planned) |                      | Y-ConJack-34<br>(Version<br>planned)   | Y-ConJack-35                    | Y-ConJack-36  |  |
|----------------------------|-------------------|---------------------|-----------------|---|----------------------|--|---------------------------------|---|--|
| Order number               | 82-00335 82-00964 |                     | 82-00346 82-007 |   | 82-00347             | 82-00348   | 82-00349                        | 82-00350  |  |
| Tray Packaging             | X                 |                     | X               |   | X                    | X  | X                               | X   |  |
| Tape and reel<br>Packaging |                   | X                   |                 | X   |                      |  |                                 |   |  |
| Type of soldering          | Through H         | lole Reflow         | Through H       | Through Hole Reflow                         |                      | Through Hole<br>Reflow   | Through Hole<br>Reflow          | Through Hole<br>Reflow  |  |
| Power contacts             | X<br>X<br>X       |                     | 2               | x   | X                    | X  |                                 | <br>X   |  |
| Transformer                |                   |                     |                 | x   |                      |  | X                               |   |  |
| Light pipes                |                   |                     | -               |   | X                    |  | x                               |   |  |
|                            |                   | 023.04              |                 |   |                      |  |                                 |   |  |
| onent<br>mponent           |                   |                     |                 | 100%  |                      | CONFIDENT  |                                 | er Drawing  |  |
|                            |                   |                     |                 | <spc></spc>                                 | Critical Dimensions. | RoHS compliant acc. to directive<br>the information contained in this draw<br>my reproduction in part or whole with<br>s prohibited. |                                 | awing subject to alteration without pr<br>HI ELECTRONICS DEUTSCHLAND<br>NCHI ELECTRONICS DEUTSCHLAI |  |
|                            |                   |                     |                 | UNLESS OTH<br>DIMENSIONS                    |                      | REVISION DESCRIPTION<br>Housing changed  | ID REV. DATE<br>T114 09.05.2022 |   |  |
|                            |                   |                     |                 | TOLERANCE                                   | S: L                 | J Updated DRW  | RIA 05.07.2018                  | YAMAI   |  |
|                            |                   |                     |                 | ISO 2768-1 m                                | ד                    | T&R pack changed   | NS 12.05.2017                   |   |  |



Yamaichi acts with all markings of the product exclusively on behalf of the customer as service provider and not as distributor. Yamaichi is not aware of the customer's end use/application. The customer indemnifies Yamaichi from any liability towards third parties in connection with the marking - with the exception of the legal exclusions of liability according to § 309 No. 7 BGB.

3

4

2

X: with com

В

С

D

E

F

1

| 100% Critical Dimensions to be inspected 100%.                   | C           | :01   | NFIC         | DENTI                                    | AL                                     | Customer Drawing         |   |  |                   |                          |                  |  |
|--|-------------|---|--------------|--|--|--------------------------|---|--|-------------------|--------------------------|------------------|--|
| Critical Dimensions.   | R           | RoHS compliant acc. to directive 2011/65/EU |              |  |  |                          | Specification/Drawing subject to alteration without prior notice. |  |                   |                          |                  |  |
| <spc> Critical Dimensions.<br/>To determine Cmk &amp; Cpk.</spc> | An          | e informa<br>y reprod<br>prohibited         | uction in pa | ined in this drawi<br>art or whole witho | ng is the<br>ut the wr                 | sole prop<br>ritten peri | perty o<br>missioi  | of YAMAICHI ELECTROI<br>n of YAMAICHI ELECTF | NICS DE<br>CONICS | EUTSCHLAND<br>DEUTSCHLAN | GMBH.<br>ND GMBH |  |
| UNLESS OTHERWISE SPECIFIED :                                     | $\triangle$ | REVISION DESCRIPTION                        |              |  | ID                                     | REV. D                   | ATE   |  |                   |                          |                  |  |
| DIMENSIONS ARE IN MILLIMETERS                                    | 023         | 023 Housing changed                         |              |  | T114                                   | 09.05.2                  | 022   |  |                   |                          | -1 11            |  |
| TOLERANCES:  |             | U Updated DRW                               |              |  | RIA                                    | 05.07.2                  | 018   |  | ٩IV               | /IAI(                    |                  |  |
| ISO 2768-1 m   | Т           | T T&R pack changed                          |              |  | NS                                     | 12.05.2                  | 017   | <b>VV</b> či i                               |                   |                          |                  |  |
| ISO 2768-2 K   | S           | S Housing changed                           |              |  |  | 09.02.2                  | 017   |  |                   |                          |                  |  |
| ORDER / ARTICLE NO. See Table                                    | R           | R L. pipe + tray upd                        |              |  | SLS                                    | 03.03.2                  |   |  |                   |                          |                  |  |
| SRDERTARTICEL NO. See Table                                      |             | DO NOT SCALE DRAWING                        |              |  | Description: Ethernet jack 90°, 8(8)+2 |                          |   |  | 8(8)+2/0          |                          |                  |  |
| ANGLE PROJECTION   |             | ID DATE                                     |              | DATE                                     |  |                          |   |  |                   |                          |                  |  |
|  |             | EATED                                       | TF           | 21.01.2010                               | Purcha                                 | se No.:                  |   |  |                   |                          |                  |  |
| F FIRST  | MO          | MODIFIED T114                               |              | 09.05.2022                               |  |                          | Y-CONJACK-3x  |  |                   |                          |                  |  |
| t-t++++ FIRSI  |             | RELEASED M189 09                            |              | 09.05.2022                               | Drawin                                 |                          |   |  |                   |                          | REVISION:        |  |
|  |             |   |              |  |  | Cι                       | JSto  | omer-P124                                    | 3A(               | )4                       | 023              |  |
| WEIGHT:  | SUB         | REV04                                       | T153         | 23.02.2024                               |  | SCAL                     | .E: 2:1   | 1 SHEET 3                                    | OF 3              | DIN A3 - A5              | SEMBLY           |  |

7

8